

IN-LINE FUSE HOLDERS



SFRT

Twist-Lock In-Line Fuseholders for FSFE fuses. Used at 32V or less with fuses rated up to 20A when proper spring for fuse size is installed.

Includes fuse listed

Standard Fuse Ampere Ratings

CATALOG	FUSE	
NUMBER	Installed	
SFRT4	FSFE4	
SFRT6	FSFE6	
SFRT7-1/2	FSFE7-1/2	
SFRT9	FSFE9	
SFRT14	FSFE14	
SFRT20	FSFE20	



SFRB

Bayonet Knob In-Line Fuseholders for FSFE fuses. Used at 32V or less with fuses rated up to 20A when proper spring for fuse size is installed.

Standard Fuse Ampere Ratings

LOG FUSE BER INSTALLED	
FSFE4 FSFE6 FSFE7-1/2 FSFE9 FSFE14	



SFRG

In-Line Fuseholder for 5 x 20mm fuses.

Max. current rating for 5x20mm fuses - 10A @ 32V



FSFE

Glass Body Fast Acting

4A through 30A, 32VAC/DC - UL Listed

CATALOG	AMPERE	VOLTS	FUSE
Number	Rating		LENGTH
FSFE4	4A	32V	5/8" 3/4" 7/8" 7/8" 1-1/16" 1-1/4" 1-7/16"
FSFE6	6A	32V	
FSFE7-1/2	7-1/2A	32V	
FSFE9	9A	32V	
FSFE14	14A	32V	
FSFE20	20A	32V	
FSFE30	30A	32V	

Standard Fuse Ampere Ratings

Catalog Number: SFRU

Universal In-Line Fuseholder - supplied with 15" loop of #14 AWG red vinyl insulated wire frame and three springs in different lengths to accommodate FSFE size fuses.